

14. (Unchanged) A method of combusting a propellant that exhibits desirable regression rate during combustion within a port having a gas stream flowing through the port, comprising the steps of:

providing a propellant having under heat transfer from the gas stream flowing through the port, a liquid layer with surface tension  $\sigma$  and liquid viscosity  $\mu_l$  values that promote entrainment of droplets from said liquid layer into said gas stream flowing in said port, and said propellant has an  $a_{onset}$  value, where  $a_{onset}$  is the entrainment onset parameter and is given by:

$$a_{onset} = 1.05 \times 10^{-2} [\rho_g^{1.3} / \rho_l^{0.3}] [1 / (0.03 C_{B1})^{0.8}] (1 / \mu_g) \sigma \mu_l^{0.6};$$

where  $\rho_g$  is the average density of the gas stream in the port,  $\rho_l$  is the average density of the propellant in the liquid layer,  $C_{B1}$  is the blowing correction coefficient and is given by:

$$C_{B1} = (2 / 2 + 1.25 B^{0.75})$$

where  $0 < B < 15$ , and  $\mu_g$  is the mean gas viscosity of the gas stream in the port, and the units of  $a_{onset}$  is  $kg^{1.6} / (m^{2.6} \cdot sec^{1.6})$ ;

flowing the gas stream through the port; and

combusting said propellant and gas wherein said propellant has a value of  $a_{onset}$  that promotes entrainment of droplets from said liquid layer into said gas stream flowing in said port.

15. (Unchanged) The method of Claim 14 wherein  $a_{onset}$  is equal to or less than approximately  $0.9 kg^{1.6} / (m^{2.6} \cdot sec^{1.6})$ .

16. (Unchanged) The method of Claim 14 wherein the propellant is selected from a n-alkane class of hydrocarbons, having the general formula of  $C_n H_{2n+2}$  and mixtures thereof, where n is a mean carbon number and is in the range of 15 to 80, and which are solid at room temperature.

17. (Unchanged) The method of Claim 14 wherein the propellant is selected from a group of alkhylnaphthalene compounds, anthracene, and mixtures thereof.

18. (Unchanged) The method of Claim 14 wherein the propellant is selected from a group of organic acids having the general formula of  $\text{CH}_3(\text{CH}_2)_n\text{COOH}$  and mixtures thereof, where  $n$  is in the range of 8 to 25.

19. (Unchanged) The method of Claim 14 wherein the propellant is selected from a group of  $n$ -paraffin compounds and mixtures thereof.

Claim 20 previously canceled.

21. (Unchanged) The method of Claim 14 wherein the propellant is selected from a group of isomers of the alkane class of hydrocarbons.

Claim 48 previously canceled.

49. (Unchanged) A method of combusting a propellant that exhibits desirable regression rate during combustion within a port having an oxidant flowing through the port, comprising the steps of:

flowing the oxidant through the port;

the propellant forming, under the heat transfer from the oxidant flowing through the port, a liquid layer having a liquid viscosity of less than about 1 milliPa-sec, and a surface tension of less than about 25 milliN/m, such that droplets from said liquid layer are entrained in said oxidant; and  
combusting said propellant and oxidant.